

Fig. 516 5 Gallon AST Spill Container

Specification Sheet



DESCRIPTION

The Fig. 516 contains any spills that occur at the fill point on Aboveground Storage Tanks. It is designed to be mounted on top of the AST. The 5 gallon Fig. 516 has a lockable hinged cover. It is of steel construction and powdercoated white inside and out. It has an optional push type drain with a fluoroelastomer o-ring.

2 Inch Male or Female With Drain	\$296.00
Without Drain	\$266.00
4 Inch Male or Female With Drain	\$318.00
Without Drain	\$288.00

SPECIFICATION OPTIONS:

- A—Capacity: Gallons
- B—Mounting Connection: Male (M), Female (F)
- C—Size: NPT Threads
- D—Drain: Yes/No
- E—Mount
- F—Height (Inches)
- G—Width (Inches)
- H—Body Diameter
- I—Shipping Weight (lbs.)
- J—ULC Listing

Body: Powdercoated White
 Lid: Powdercoated White
 Other Hardware: Zinc Plated Steel

Optional With Drain:
 Drain Push Rod: Brass
 Drain Nut: Brass
 Spring: Bronze
 O-Ring: Fluoroelastomer

Black Powdercoat Optional

ID Number	B	C	D	E	F	G	H	I	J
516---0200 ACPW	F	2	No	Centered	12.03	17.2	13.2	17	Yes
516---0400 ACPW	F	4	No	Centered	13.41	17.2	13.2	21	Yes
516D--0200 ACPW	F	2	Yes	Centered	13.16	17.2	13.2	17	Yes
516D--0400 ACPW	F	4	Yes	Centered	13.41	17.2	13.2	21	Yes
516O--0200 ACPW	F	2	No	Offset	12.03	17.2	13.2	17	Yes
516O--0400 ACPW	F	4	No	Offset	13.41	17.2	13.2	21	Yes
516OD-0200 ACPW	F	2	Yes	Offset	13.16	17.2	13.2	17	Yes
516OD-0400 ACPW	F	4	Yes	Offset	13.41	17.2	13.2	21	Yes
516M--0200 ACPW	M	2	No	Centered	12.28	17.2	13.2	16.5	Yes
516M--0400 ACPW	M	4	No	Centered	13.78	17.2	13.2	19	Yes
516MD-0200 ACPW	M	2	Yes	Centered	13.28	17.2	13.2	17.5	Yes
516MD-0400 ACPW	M	4	Yes	Centered	13.78	17.2	13.2	20.5	Yes
516MO-0200 ACPW	M	2	No	Offset	12.28	17.2	13.2	17	Yes
516MO-0400 ACPW	M	4	No	Offset	13.78	17.2	13.2	19	Yes
516MOD0200 ACPW	M	2	Yes	Offset	13.28	17.2	13.2	17.5	Yes
516MOD0400 ACPW	M	4	Yes	Offset	13.78	17.2	13.2	20.5	Yes