

Fig. 244 8" Emergency Vents

Specification Sheet

UL Listed Emergency vent (pressure relief only) used on aboveground storage tanks, as a code requirement, to help prevent the tank from becoming over-pressurized and possibly rupturing if ever exposed to fire. Vent must be used in conjunction with a "normal vent." Correct application of this vent requires proper vent size and selection for the tank system in order to meet the specific venting capacity.

Morrison Bros emergency vents conform to the following codes and standards: API 2000, International Fire Code, National Fire Code of Canada, NFPA 1, 30, 30A, 31, 37, 110, PEI RP200, PEI RP800, Underwriters Laboratories Inc., UL-142 UL-2085 UL- 2244, Underwriters Laboratories of Canada CAN/ULC S601-07, CAN/ULC S602-07, CAN/ULC S652-08.

Additional References: NFPA 30, UL 142, Morrison Venting Guide.



I.D. Number	A	B	C	D	E	F	G	Diameter	Height	Weight
244O--0600 AV	8	504,818		8	I	A	AL	11	4.6	33
244O--0600 AVEVR	8	504,818		8	I	B	AL	11	4.6	33
244O--0700 AV	8	504,818		16	I	A	AL	11	5.8	62
244O--0700 AVEVR	8	504,818		16	I	B	AL	11	5.8	62
244OI-0600 AV	8	504,818		8	I	A	I	11	4.6	39
244OF-0100 AV	8	504,818	F	8	I	A	AL	11	3.3	33
244OF-0100 AVE	8	504,818	F	8	I	B	AL	11	3.3	33
244OF-0200 AV	8	504,818	F	16	I	A	AL	11	4.5	67
244OF-0200 AVE	8	504,818	F	16	I	B	AL	11	4.5	67
244OM-0600 AV	8	504,818	M	8	I	A	AL	11	5.8	34
244OM-0600 AVEVR	8	504,818	M	8	I	B	AL	11	5.8	34
244OM-0700 AV	8	504,818	M	16	I	A	AL	11	6.9	63
244OM-0700 AVEVR	8	504,818	M	16	I	B	AL	11	6.9	63
244OMB0700 AV	8	504,818	M	16	I	A	AL	11	6.9	63
244OMBSP0600 AV	8	504,818	M	8	I	B	AL	11	5.8	34
244OMI0600 AV	8	504,818	M	8	I	A	I	11	5.8	42
244OMI0700 AV	8	504,818	M	16	I	A	I	11	6.9	71

Flange = 14" OD ; eight (8) .88" Diameter holes on 11.75" diameter B.C.

CHART KEY:

- A**—Size: 8"
- B**—Venting Capacity/CFH (in 1000's)
- C**—Mounting Connection: Female N.P.T. (BLANK); Male N.P.T.(M); Flanged (F);
- D**—Pressure Settings: 8, 16 oz/in². Pressure Required to Open Vent.
- E**—Cover: Cast Iron Powder Coated (I)
- F**—Seat Material: O-Ring Viton A (A) or Viton B (B)
- G**—Body Material: Aluminum (AL) or Iron (I)
- Diameter**—Dimension Across Vent
- Height**—Dimension From Base to Top When Closed
- Weight**—Shipping Weight
- Bolt**—Zinc plated steel

WARNING: DO NOT FILL OR UNLOAD FUEL FROM A STORAGE TANK UNLESS IT IS CERTAIN THAT THE TANK VENTS WILL OPERATE PROPERLY. Morrison tank vents are designed only for use on shop fabricated atmospheric tanks which have been built and tested in accordance with UL 142, NFPA 30 & 30A, and API 650 and in accordance with all applicable local, state, and federal laws. In normal operation, dust and debris can accumulate in vent openings and block air passages. Certain atmospheric conditions such as a sudden drop in temperature, below freezing temperatures, and freezing rain can cause moisture to enter the vent and freeze which can restrict internal movement of vent mechanisms and block air passages. All storage tank vent air passages must be completely free of restriction and all vent mechanisms must have free movement in order to insure proper operation. Any restriction of airflow can cause excessive pressure or vacuum to build up in the storage tank, which can result in structural damage to the tank, fuel spillage, property damage, fire, injury, and death. Monthly inspection, and immediate inspection during freezing conditions, by someone familiar with the proper operation of storage tank vents, is required to insure venting devices are functioning properly before filling or unloading a tank.