

Morrison Bros. Co.
Fig. 244A & 244C
Specification Sheet

Both the 244A Flanged Adaptor and the 244C Companion Flange can be used with either a 244F Emergency Vent or a 143A Pressure/Vacuum Emergency Vent.

The 244A Adaptor end should be welded to the top of a steel aboveground storage tank.

The 244C threads on to a male pipe nipple mounted or welded to the top of an aboveground storage tank.



244C Companion Flange



244A Flanged Adaptor

SPECIFICATION OPTIONS:

I.D. NUMBER	A	B	C	D	E	F	DIA	HT	WT.
244A--0000 1A	6"	CS	8	7/8"	11½"	NA	11"	8"	12
244A--0100 1A	8"	CS	8	7/8"	11¾"	NA	13¾"	8"	19
244A--0200 1A	10"	CS	12	1"	14¼"	NA	16"	8"	20
244C--0100 1F	8"	CI	8	7/8"	11¾"	8"	13½"	1 ¹ / ₈ "	27
244C--0200 1F	10"	CI	12	7/8"	14¼"	10"	16"	1 ³ / ₁₆ "	36

CHART KEY:

- A**—Size
- B**—Construction: Carbon Steel (CS); Cast Iron (CI)
- C**—Number of Holes
- D**—Size of Holes
- E**—Size of Bolt Circle
- F**—NPT I.D.
- Diameter**—Dimension Across
- Height**—Dimension From Base to Top
- Weight**—Shipping Weight