

# Model 244A & 244C Flange Adaptor and Companion Flange

SPECIFICATION SHEET

244A Flange adaptors are welded to tank top openings in aboveground storage tanks creating a flanged emergency vent connection.

244C Female threads designed to convert a male threaded pipe nipple to a 150# raised face flange connection.

## Features

### 244A

- Pre-drilled for easy installation of emergency vent
- Gaskets, nuts, and bolts are available

## Construction Details

- 244A is carbon steel
- 244C is cast iron



244A (4")



244C (8")

I.D. Number	A	B	C	D	E	F	Diameter	Height	Weight
244A--0400 1A	4"	CS	8	3/4"	7 1/2"	NA	9"	6"	8.0
244A--0000 1A	6"	CS	8	7/8"	11 1/2"	NA	11"	8"	12.0
244A--0100 1A	8"	CS	8	7/8"	11 3/4"	NA	13 3/4"	8"	19.0
244A--0200 1A	10"	CS	12	1"	14 1/4"	NA	16"	8"	20.0
244C--0100 1F	8"	CI	8	7/8"	11 3/4"	8"	13 1/2"	1 1/8"	27.0
244C--0200 1F	10"	CI	12	7/8"	14 1/4"	10"	16"	1 3/16"	36.0

### SPECIFICATION OPTIONS:

**A**—Size  
**B**—Construction: Carbon steel (CS); Cast iron (CI)  
**C**—Number of holes  
**D**—Size of holes  
**E**—Size of bolt circle  
**F**—NPT I.D.  
**Diameter**—Dimension across  
**Height**—Dimension from base to top  
**Weight**—Shipping weight

570 E. 7th Street, P.O. Box 238 | Dubuque, IA 52004-0238

t. 563.583.5701 | 800.553.4840 | f. 563.583.5028

www.morbros.com