

Fig. 419 Drop Tube

Specification Sheet



The Fig. 419 Drop Tube directs product flow to liquid level when filling a storage tank. The drop tube prevents free fill and reduces agitation of liquid when filling. The flanges fits between tight fill adaptor riser pipe. The tube extends to near bottom for submerged fill.

All Morrison Drop Tubes are extruded aluminum.

The 2" and 3" drop tubes can also be attached to the Morrison Fig. 9095A AST Overfill Prevention Valve.

EVR approved models available.

SPECIFICATION OPTIONS:

- A—Size
- B—Aluminum (AL) or Anodized (AN)
- C—Flange OD
- D—Flange OD + / -
- E—Tube ID
- F—Tube ID + / -
- G—Wall
- H—Wall + / -
- I—OAL Length
- WT.—Weight (Lb.)

I.D. Number	A	B	C	C	E	F	G	H	I	WT.
419---0600 1T	2" x 4'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	4 feet	1.75
419---0700 1T	2" x 6'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	6 feet	2.5
419---0100 1T	2" x 12'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	12 feet	5
419---0200 1T	3" x 10'	AL	3.31"	0.015	2.946	0.015	0.063	0.003	10 feet	6.6
419---1400 1T	3" x 12'	AL	3.31"	0.015	2.946	0.015	0.063	0.003	12 feet	9
419---1000 1T	4" x 4'	AL	4.22"	0.015	3.875	0.023	0.062	0.007	4 feet	5.5
419---0900 1T	4" x 5'	AL	4.22"	0.015	3.875	0.023	0.062	0.007	5 feet	6
419---0800 1T	4" x 7'	AL	4.22"	0.015	3.875	0.023	0.062	0.007	7 feet	7.5
419---0300 1T	4" x 10'	AL	4.22"	0.015	3.875	0.023	0.062	0.007	10 feet	9
419---0400 1T	4" x 12'	AL	4.22"	0.015	3.875	0.023	0.062	0.007	12 feet	12
419---0500 1T	4" x 15'	AL	4.22"	0.015	3.875	0.023	0.062	0.007	15 feet	10.5
419---02041TEVR	2" x 4'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	4 feet	1.75
419---02061TEVR	2" x 6'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	6 feet	2.5
419---02121TEVR	2" x 12'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	12 feet	5
419---03101TEVR	3" x 10'	AL	3.31"	0.015	2.946	0.015	0.063	0.003	10 feet	6.6
419---03121TEVR	3" x 12'	AL	3.31"	0.015	2.946	0.015	0.063	0.003	12 feet	9
419A--02041TEVR	2" x 4'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	4 feet	1.75
419A--02061TEVR	2" x 6'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	6 feet	2.5
419A--02121TEVR	2" x 12'	AL	2.2"	0.015	1.906	+ 0.062 -0.000	0.062	+ 0.006 -0.010	12 feet	5
419A--03101TEVR	3" x 10'	AL	3.31"	0.015	2.946	0.015	0.063	0.003	10 feet	6.6
419A--03121TEVR	3" x 12'	AL	3.31"	0.015	2.946	0.015	0.063	0.003	12 feet	9
419A--0500 1TA	4" x 15'	AN	4.22"	0.015	3.875	0.023	0.062	0.007	15 feet	10.5