

# 515SD AST Remote Spill Container

## Specification Sheet

For use on aboveground storage tanks for the purpose of containing fuel spillage during remote tank filling operations.

- Available in single 2", 3", and 4" versions or double 2" and 3".
- 22½" wide x 24" deep—container height 24½".
- 15 gallon capacity.
- Weather-tight enclosure.
- Container continuously vents to prevent buildup of vapors and internal pressure.
- ½" NPT drain with stainless steel locking ball valve.
- Single column base—adjustable height 30"—48". Base to center line of pipeline (+/- 1½").
- Base plate with four ½" mounting holes.
- Lockable lid.
- Container can hold up to two 2" or 3" Morrison swing check valves, ball valves, quick couplers, and dust caps.
- 2" bung for pump.
- Gas cylinder holds lid open during use.



### SPECIFICATION OPTIONS:

- B—Pipe Mounting Connection: Female (F)  
 C—Size: Female NPT Threads  
 D—Drain: Yes/No  
 E—Width (Inches) (+/- ½")  
 F—Depth (+/- ½")  
 G—Shipping Weight (lbs.)

ID Number	B	C	D	E	F	G
515SD-0200 AC	F	2"	Yes	23"	24"	155
515SD-0300 AC	F	3"	Yes	23"	24"	156
515SD-0400 AC	F	4"	Yes	23"	24"	157
515SD-2200 AC	F	2" & 2"	Yes	23"	24"	159
515SD-2300 AC	F	3" & 3"	Yes	23"	24"	160

- Body: 304 stainless steel  
 Lid: 304 stainless steel  
 Flange Hardware: Zinc plated steel  
 Flange Adaptor: 304 stainless steel  
 Gasket: Teflon

