

Model 515SD Series AST Remote Spill Container

SPECIFICATION SHEET

Application

Remote fill containers provide containment for small spills that may occur at the fill point during remote filling operations.

Features and Details

- Single connections in 2", 3" or 4" female threads
- Dual connections in 2" or 3" (may be combined)
- 15 gallon capacity
- Gas spring cylinder holds the lid in the up position when fueling
- Lockable with a padlock
- Weather-tight enclosure
- Vented cover
- 2" female threaded return pump connection
- Integrated sump drain with ½" with locking ball valve
- Container 22½" wide x 24" deep x 24¼" height
- Four leg stand ships knocked down and requires minimal assembly

Materials of Construction

- Container and lid... 12 gauge stainless steel
- Pipe connection... stainless steel
- Pedestal mount... schedule 40 stainless steel pipe
- Adjustable four leg stand... 10 gauge stainless steel
- Ball valve... stainless
- Flange connection gasket... Teflon®

Code Compliance

CAN-ULC-S663-11*; Florida DEP EQ 535

**Low profile stand excluded from listing.*



515SD



515SDST



515SD shown on
515STSL0000 AS

Item numbers and drawings on next page...



Item Number	A	B	C	D	E	F	G
515SD-0200 AC	P	1	2"	Yes	23"	24"	155.0
515SD-0300 AC	P	1	3"	Yes	23"	24"	156.0
515SD-0400 AC	P	1	4"	Yes	23"	24"	157.0
515SD-2200 AC	P	2	2" & 2"	Yes	23"	24"	159.0
515SD-2300 AC	P	2	3" & 3"	Yes	23"	24"	160.0
515SD-3200 AC	P	2	2" & 3"	Yes	23"	24"	160.0
515SD-0200 ACO	N	1	2"	Yes	23"	24"	155.0
515SD-0300 ACO	N	1	3"	Yes	23"	24"	156.0
515SD-0400 ACO	N	1	4"	Yes	23"	24"	157.0
515SD-2200 ACO	N	2	2" & 2"	Yes	23"	24"	159.0
515SD-2300 ACO	N	2	3" & 3"	Yes	23"	24"	160.0
515SDST0200 AC	S	1	2"	Yes	23"	24"	
515SDST0300 AC	S	1	3"	Yes	23"	24"	
515SDST0400 AC	S	1	4"	Yes	23"	24"	
515SDST2200 AC	S	2	2" & 2"	Yes	23"	24"	
515SDST2300 AC	S	2	3" & 3"	Yes	23"	24"	
515ST-0100 AS	Four leg adjustable stand, powder coated						
515STS0100 AS	Four leg adjustable stand, stainless steel						
515STSL0100 AS	Four leg, low profile stand, stainless steel						

SPECIFICATION OPTIONS:

- A**—Mounting connection: Pedestal mount (P), four leg stand (S), NO post or stand (N)
- B**—Number of ports
- C**—Size: Female NPT threads
- D**—Drain: Yes (Y), No (N)
- E**—Width (inches) (+/- 1/2")
- F**—Depth (inches) (+/- 1/2")
- G**—Shipping weight (lbs)

*Order low profile stand and fill box separately.

