



Model 517 Series 3½ Gallon AST Spill Container

SPECIFICATION SHEET

Application

Tank top spill containers are designed to contain small spills that occur at the fill point on aboveground storage tanks.

Features and Details

- 3½ gallon (13.25 liters) capacity
- Hinged cover is lockable with a padlock
- Centered connection
- **517** has male threaded inlet and outlet
- **517F** has female threaded inlet and outlet
- **517WO** includes removable screen for use as used oil collection point, male threads

Materials of Construction

- 16 gauge spun steel, powder coated white body and cover

Code Compliance

- Florida DEP EQ 345, meets the new and revised requirements for CAN-ULC-S663-11 (effective September 25, 2015)



Item Number	A	B	C	D	E	F	G	H	I	J
517---0100 AC	3½	M	C	2"	N	N	8½"	17¼"	9.0	13 ⁹ / ₆₄ "
517---0200 AC	3½	M	C	4"	N	N	8 ⁵ / ₈ "	17¼"	9.0	13 ⁹ / ₆₄ "
517---2500 ACPW	3½	M	C	2½"	N	N	8 ¹³ / ₃₂ "	17¼"	9.0	13 ⁹ / ₆₄ "
517F--0100 AC	3½	F	C	2"	N	N	8"	17¼"	10.50	13 ⁹ / ₆₄ "
517F--0200 AC	3½	F	C	4"	N	N	10½"	17¼"	10.50	13 ⁹ / ₆₄ "
517F--2500 ACPW	3½	F	C	2½"	N	N	8 ¹³ / ₃₂ "	17¼"	10.50	13 ⁹ / ₆₄ "
517WO-0100 AC	3½	M	C	2"	N	Y	8½"	17¼"	11.0	13 ⁹ / ₆₄ "
517WO-0200 AC	3½	M	C	4"	N	Y	8 ⁴¹ / ₆₄ "	17¼"	11.0	13 ⁹ / ₆₄ "

SPECIFICATION OPTIONS:

- A—Capacity: Gallons
- B—Mounting connection: Male (M), Female (F)
- C—Mounting location: Center (C)
- D—Size: NPT threads
- E—Drain: Yes/No
- F—Screen: Yes/No
- G—Height: (inches)
- H—Width: (inches)
- I—Shipping weight: (lbs)
- J—Body diameter (inches)

