



Remote Strobe Features

- Compact rotating warning light
- Single retaining screw allows for quick and easy access for inspection and relamping
- Water-resistant
- Indoor and outdoor applications

Remote Horn Features

- Produces a loud horn tone by the electro-mechanical vibration of a diaphragm (100dB at 10 feet)
- Excellent for general alarm in areas of high ambient noise levels
- Enclosed in a zinc die-cast housing and sealed with grey powder-coat paint
- Compact size and heavy-duty construction

Remote Horn with Strobe Features

- Units can either independently or simultaneously wired with the audible device
- Recommended for use in industrial applications and situations where effective visual warning is needed
- Compact size
- Indoor and outdoor applications

Conduit Junction Housing Features

- Act as pull and splice boxes
- Connect lengths of conduit
- Provide access to connectors for maintenance and future changes
- Act as pull outlets for connectors being installed
- 1/2" conduit connection

Code Compliance

- **Remote Strobe:** UL and cUL Listed
- **Remote Horn:** UL and cUL Listed; CSA listed (File No. 005835, Model 350) and FM Approved
- **Remote Horn with Strobe:** UL Listed; CSA listed (File No. 005835, Model VALS)
- **925---0113 2B:** UL and cUL Listed; NEMA 4
- **925---0114 2B:** UL Listed; NEC/CEC: Class I, Division 1 & 2, Groups C, D; Class II, Division 1, Groups E, F, G; Class II, Division 2, Groups F, G; Class III; ANSI Standard: C33.27; CSA listed (File No. 013046, Model GUAB); NEMA 3, 4, 7CD, 9EFG





Model 918AC/1218 Alarm and Sensor Accessories (continued)

SPECIFICATION SHEET

Item Number	Description	Voltage	Operating Current	Weight (lbs)
918AC-0156 2L	Remote strobe	120VAC 50/60HZ	0.22 amps	2.70
918AC-0154 AH	Remote horn	120VAC 50/60Hz	0.18 amps	1.50
918AC-0157 AHS	Remote horn with strobe	120 VAC 50/60HZ	0.24 amps	1.75
925---0113 2B	LB Conduit junction box	N/A	N/A	0.50
925---0114 2B	GUAB conduit junction box	N/A	N/A	2.25

