



Model 934 Single Poppet Foot Valve with Expansion Relief

NEW PRODUCT ANNOUNCEMENT

Application

Single poppet foot valves are installed at the inlet of a suction line normally at the bottom of the storage tank as a prime holding valve.

Features and Details

- Expansion relief: 25 PSI
- Opening pressure: less than 1 PSI
- Maximum working pressure: 200 PSI
- Working temperature: -40°F to 300°F
- 20 mesh inlet screen used to help filter debris from collecting on the seats

Materials of Construction

- Body... 304/316 series stainless steel
- Screen... 304 stainless steel
- Seals... Viton® GF

Item Number	Size	Threads	Max OD	Height	Weight (lbs)	List Price
934--10500 AV	½"	NPT	1.43"	5.5"	0.87	\$150.00
934--10700 AV	¾"	NPT	1.43"	5.7"	1.03	\$165.00
934--11000 AV	1"	NPT	1.66"	6.6	1.75	\$180.00
934B-10500 AV	½"	BSP	1.43"	5.5"	1.0	\$150.00
934B-10700 AV	¾"	BSP	1.43"	5.7"	1.0	\$165.00
934B-11000 AV	1"	BSP	1.66"	6.6	1.75	\$180.00
934---0500 AS	½"	Suction pipe strainer only			.20	\$25.00
934---0700 AS	¾"	Suction pipe strainer only			.30	\$32.00
934---1000 AS	1"	Suction pipe strainer only			.45	\$39.00

